



336 WEST FRONT STREET P.O. BOX 4004 BURLINGTON, NORTH CAROLINA 27215 PHONE (336) 227-7710 • FAX (336) 227-1175 www.diversifiedtestinglabs.com "We Test Per Your Request"-

September 3, 2020

Mr. Nathan Wintermute MERMET 5970 N. Main Street Cowpens, SC 29330

Reference: Laboratory Test Report Lab Identification No. 42526 Invoice No. 73781

Dear Mr. Wintermute:

One (1) sample, identified as **NATTÉ™ 3%**, was received and tested in accordance with the National Fire Protection Association No. 701, "Standard Methods of Fire Tests for Flame Propagation of Textiles and Films, 2019 Edition, (Test 1)". The results are as follows:

	<u>Test Results</u>	
Specimen Number	<u>Residual Flame</u> (seconds)	<u>Weight Loss</u> (percent)
1	0.0	7.61
2	0.0	6.76
3	0.0	7.37
4	0.0	5.47
5	0.0	7.02
6	0.0	6.84
7	0.0	7.65
8	0.0	6.70
9	0.0	7.05
<u>10</u>	<u>0.0</u>	<u>6.26</u>
AVG	0.0	6.87

The fabric sample submitted **meets** the minimum requirements of the above standard. The average percent weight loss cannot exceed 40% and the weight loss of individual specimens cannot exceed mean value plus three standard deviations. The average residual flame cannot exceed 2.0 seconds.


If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Brian S. Dement

BSD/mr





DIVERSIFIED TESTING LABORATORIES, INC.

336 WEST FRONT STREET P.O. BOX 4004 BURLINGTON, NORTH CAROLINA 27215 PHONE (336) 227-7710 • FAX (336) 227-1175 www.diversifiedtestinglabs.com "We Test Per Your Request"-

March 21, 2017

Mr. Lance Bracey MERMET 5970 N. Main Street Cowpens, SC 29330

Reference: Laboratory Test Report Lab Identification No. 24340 Invoice No. 55501

Dear Mr. Bracey:

One (1) sample, identified as **NATTE 5%**, was received and tested in accordance with the National Fire Protection Association No. 701, "Standard Methods of Fire Tests for Flame Propagation of Textiles and Films, 2015 Edition, (Test 1, Small Scale)". The results are as follows:

Test Results				
Specimen Number	<u>Residual Flame</u> (seconds)	<u>Weight Loss</u> (percent)		
1	0.0	6.63		
2	0.0	6.00		
3	0.0	6.83		
4	0.0	7.04		
5	0.0	6.79		
6	0.0	6.07		
7	0.0	7.31		
8	0.0	7.56		
9	0.0	6.77		
<u>10</u>	<u>0.0</u>	<u>7.59</u>		
AVG	0.0	6.86		

The sample submitted **meets** the minimum requirements of the above standard. The average percent weight loss cannot exceed 40% and the weight loss of individual specimens cannot exceed mean value plus three standard deviations. The average residual flame cannot exceed 2.0 seconds.


If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Brian S. Dement

BSD/mr





DIVERSIFIED TESTING LABORATORIES, INC.

336 WEST FRONT STREET P.O. BOX 4004 BURLINGTON, NORTH CAROLINA 27215 PHONE (336) 227-7710 • FAX (336) 227-1175 www.diversifiedtestinglabs.com "We Test Per Your Request"-

March 21, 2017

Mr. Lance Bracey MERMET 5970 N. Main Street Cowpens, SC 29330

Reference: Laboratory Test Report Lab Identification No. 24340 Invoice No. 55501

Dear Mr. Bracey:

One (1) sample, identified as **NATTE 10%**, was received and tested in accordance with the National Fire Protection Association No. 701, "Standard Methods of Fire Tests for Flame Propagation of Textiles and Films, 2015 Edition, (Test 1, Small Scale)". The results are as follows:

Test Results				
Specimen Number	<u>Residual Flame</u> (seconds)	<u>Weight Loss</u> (percent)		
1	0.0	7.11		
2	0.0	7.77		
3	0.0	7.65		
4	0.0	7.74		
5	0.0	7.74		
6	0.0	7.53		
7	0.0	8.06		
8	0.0	8.04		
9	0.0	7.88		
<u>10</u>	<u>0.0</u>	<u>7.72</u>		
AVG	0.0	7.72		

The sample submitted **meets** the minimum requirements of the above standard. The average percent weight loss cannot exceed 40% and the weight loss of individual specimens cannot exceed mean value plus three standard deviations. The average residual flame cannot exceed 2.0 seconds.

If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Brian S. Dement

BSD/mr

